

(12) **United States Patent**
Stevens et al.

(10) **Patent No.:** **US 8,133,230 B2**
(45) **Date of Patent:** **Mar. 13, 2012**

(54) **BONE ALIGNMENT IMPLANT AND METHOD OF USE**

(75) Inventors: **Peter M. Stevens**, Salt Lake City, UT (US); **Daniel F. Justin**, Logan, UT (US)

(73) Assignee: **Peter M. Stevens**, Salt Lake City, UT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 981 days.

(21) Appl. No.: **12/051,152**

(22) Filed: **Mar. 19, 2008**

(65) **Prior Publication Data**

US 2008/0161816 A1 Jul. 3, 2008

Related U.S. Application Data

(62) Division of application No. 10/310,720, filed on Dec. 4, 2002, now Pat. No. 7,811,312.

(51) **Int. Cl.**
A61B 5/00 (2006.01)

(52) **U.S. Cl.** **606/87**

(58) **Field of Classification Search** 606/280-299,
606/70-71, 75

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,561,550 A *	7/1951	Wright	606/67
3,741,205 A	6/1973	Markolf et al.	
3,939,828 A	2/1976	Mohr	
3,988,783 A	11/1976	Treace	
4,219,015 A	8/1980	Steinemann	
4,434,796 A	3/1984	Karapetian	

4,454,875 A	6/1984	Pratt
4,502,475 A	3/1985	Weigle
4,503,848 A	3/1985	Caspar et al.
4,570,623 A	2/1986	Ellison
4,790,297 A	12/1988	Lugue
4,841,960 A	6/1989	Garner
4,848,328 A	7/1989	Laboureau

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0486762 B1 5/1992

(Continued)

OTHER PUBLICATIONS

Cary H. Mielke, M.D., et al., *Hemiepiphyseal Stapling for Knee Deformities in Children Younger than 10 Years: A Preliminary Report*, Journal of Pediatric Orthopaedics, vol. 16, No. 4, 1996, pp. 423-429.

Peter M. Stevens, M.D., et al., *Physseal Stapling for Idiopathic Genu Valgum*, Journal of Pediatric Orthopaedics, vol. 19, No. 5, 1999, pp. 645-649.

(Continued)

Primary Examiner — Eduardo C Robert


Assistant Examiner — Mary Hoffman

(74) *Attorney, Agent, or Firm* — Workman Nydegger

(57) **ABSTRACT**

A method for correcting an angular deformity in a bone includes inserting a guide wire within a physis of a bone having an angular deformity, the physis extending between a first side the bone on which the guide wire is inserted and an opposing second side of the bone. The guide wire is used to guide a link to the physis. The link is then secured to the first side of the bone so that the link spans across the physis and restricts the growth of the physseal tissue of the physis on the first side of the bone. The physis is then allowed to generate more physseal tissue on the second side of the bone than on the first side of the bone so that the angular deformity of the bone is reduced.

16 Claims, 22 Drawing Sheets



US 8,133,230 B2

Page 2

U.S. PATENT DOCUMENTS

4,852,558 A 8/1989 Outerbridge
 4,905,679 A 3/1990 Morgan
 4,966,599 A 10/1990 Pollock
 5,041,113 A 8/1991 Biedermann et al.
 5,053,038 A 10/1991 Sheenan
 5,092,866 A * 3/1992 Breard et al. 606/54
 5,180,393 A 1/1993 Commarmond
 5,190,545 A 3/1993 Corsi
 5,304,210 A 4/1994 Crook
 5,360,450 A 11/1994 Giannini
 5,366,479 A 11/1994 McGarry
 5,372,598 A 12/1994 Luhr et al.
 5,380,324 A 1/1995 Miller
 5,387,213 A * 2/1995 Breard et al. 606/254
 5,395,372 A * 3/1995 Holt et al. 606/86 B
 5,423,826 A 6/1995 Coates et al.
 5,449,359 A 9/1995 Groiso
 D364,462 S * 11/1995 Michelson D24/145
 5,470,333 A 11/1995 Ray
 5,474,553 A 12/1995 Baumgart
 5,569,250 A 10/1996 Sarver
 5,586,985 A 12/1996 Putnam et al.
 5,603,713 A 2/1997 Aust et al.
 D378,409 S * 3/1997 Michelson D24/145
 5,607,430 A 3/1997 Bailey
 5,616,144 A 4/1997 Yapp et al.
 5,662,655 A * 9/1997 Laboureau et al. 606/75
 5,676,667 A 10/1997 Hausman
 5,681,309 A * 10/1997 Ross et al. 606/56
 5,688,283 A 11/1997 Knapp
 5,709,686 A 1/1998 Talos
 5,733,287 A 3/1998 Tepic
 5,735,875 A 4/1998 Bonutti
 5,746,742 A 5/1998 Runciman
 5,766,173 A * 6/1998 Ross et al. 606/56
 5,766,251 A * 6/1998 Koshino 623/11.11
 5,776,132 A * 7/1998 Blyakher 606/56
 5,785,712 A 7/1998 Runciman et al.
 5,785,713 A 7/1998 Jobe
 5,788,698 A 8/1998 Savornin
 5,904,683 A 5/1999 Pohndorf et al.
 5,941,879 A * 8/1999 Walulik et al. 606/54
 5,947,999 A 9/1999 Groiso
 5,951,557 A 9/1999 Luter
 5,968,046 A 10/1999 Castleman
 6,001,099 A 12/1999 Huebner
 6,004,323 A 12/1999 Park
 6,008,433 A * 12/1999 Stone 623/20.14
 6,017,345 A 1/2000 Richelsoph
 6,045,552 A 4/2000 Zucherman et al.
 6,053,919 A 4/2000 Talos
 6,139,550 A 10/2000 Michelson
 6,159,213 A 12/2000 Rogozinski
 6,187,009 B1 2/2001 Herzog
 6,214,012 B1 4/2001 Karpman et al.
 6,235,034 B1 5/2001 Bray
 6,299,613 B1 * 10/2001 Ogilvie et al. 606/279
 6,325,805 B1 * 12/2001 Ogilvie et al. 606/75
 6,379,364 B1 4/2002 Brace
 6,440,131 B1 8/2002 Haidukewych
 6,454,769 B2 9/2002 Wagner
 6,458,133 B1 10/2002 Lin
 D469,532 S 1/2003 Bryant et al.
 6,565,570 B2 5/2003 Sterett et al.
 6,565,571 B1 5/2003 Jackowski et al.
 6,585,769 B1 7/2003 Muhanna et al.
 6,669,700 B1 12/2003 Farris et al.
 6,695,846 B2 2/2004 Richelsoph et al.
 6,730,091 B1 5/2004 Pfefferle et al.
 6,740,088 B1 5/2004 Kozak et al.
 6,746,450 B1 * 6/2004 Wall et al. 606/280
 6,755,832 B2 6/2004 Happonen et al.
 6,764,489 B2 7/2004 Ferree
 6,773,437 B2 * 8/2004 Ogilvie et al. 606/75
 6,793,658 B2 9/2004 LeHuec et al.
 6,823,871 B2 * 11/2004 Schmieding 128/898
 6,830,571 B2 * 12/2004 Lenke et al. 606/250

7,048,739 B2 5/2006 Konieczynski et al.
 7,481,830 B2 * 1/2009 Wall et al. 606/297
 7,909,857 B2 * 3/2011 Ogilvie et al. 606/279
 2001/0014807 A1 8/2001 Wagner
 2001/0037112 A1 11/2001 Brace
 2002/0058939 A1 5/2002 Wagner
 2002/0077630 A1 6/2002 Lin
 2003/0004515 A1 1/2003 Curtin
 2004/0019353 A1 1/2004 Freid et al.
 2004/0181226 A1 9/2004 Michelson
 2005/0149023 A1 7/2005 Ritland
 2006/0142767 A1 * 6/2006 Green et al. 606/69
 2010/0004652 A1 * 1/2010 Green et al. 606/70

FOREIGN PATENT DOCUMENTS

EP 0598573 A2 5/1994
 EP 0599640 B1 8/1998
 EP 0684017 B1 2/1999
 FR 2 709 410 3/1995
 TW 537025 6/2003
 WO WO 93/03681 A1 3/1993
 WO WO 00/22999 4/2000
 WO WO 01/03570 1/2001
 WO WO 01/19267 A1 3/2001
 WO WO 01/91660 A1 12/2001
 WO WO 2007/044391 A2 4/2007

OTHER PUBLICATIONS

Andrea Kramer, M.D., et al., *Anterior Femoral Stapling*, Journal of Pediatric Orthopaedics, vol. 21, No. 6, 2001, pp. 804-807.
 J. Richard Bowen, M.D. et al., *Partial Epiphysiodesis at the Knee to Correct Angular Deformity*, Clinical Orthopaedics and Related Research, No. 198, Sep. 1985, pp. 184-190.
 S.T. Canale, M.D. et al., *Percutaneous Epiphysiodesis: Experimental Study and preliminary Clinical Results*, Journal of Pediatric Orthopaedics, vol. 6, No. 2, 1986, pp. 150-156.
 James W. Ogilvie, M.D., *Epiphysiodesis: Evaluation of a new Technique*, Journal of Pediatric Orthopaedics, vol. 6, No. 2, 1986, pp. 147-149.
 D. B. Phemister, *Operative Arrestment of Longitudinal Growth of Bones in the treatment of Deformities*, The Journal of Bone and Joint Surgery, vol. XV, No. 1, Jan. 1933, pp. 1-15.
 Walter P. Blount, M.D., et al., *Control of Bone Growth by Epiphyseal Stapling: A Preliminary Report*, The Journal of Bone and Joint Surgery, vol. 31-A, No. 3, Jul. 1949, pp. 646-478, 953.
 Walter P. Blount, M.D., *A Mature Look at Epiphyseal Stapling*, Clinical Orthopaedics and Related Research, Section II, No. 77, Jun. 1971, pp. 159-163.
 Charles H. Frantz, M.D., *Epiphyseal Stapling: A Comprehensive Review*, Clinical Orthopaedics and Related Research, No. 77, Jun. 1971, pp. 149-157.
 R.K. Fraser et al., *Medial Physeal Stapling for Primary and Secondary Genu Valgum in Late Childhood and Adolescence*, The Journal of Bone and Joint Surgery, vol. 77-B, No. 5, Sep. 1995, pp. 733-735.
 Jean-Paul Metaizeau, M.D., et al., *Percutaneous Epiphysiodesis Using Transphyseal Screws (PETS) [Limb-Length Discrepancy]*, Journal of Pediatric Orthopaedics, vol. 18, No. 3, May/Jun. 1998.
 Office Action dated Sep. 5, 2008 issued in U.S. Appl. No. 11/244,879.
 Office Action dated Apr. 16, 2009 issued in U.S. Appl. No. 11/244,879.
 Office Action dated Mar. 1, 2006 issued in U.S. Appl. No. 10/310,720.
 Office Action dated Jul. 26, 2006 issued in U.S. Appl. No. 10/310,720.
 Office Action dated Jan. 30, 2007 issued in U.S. Appl. No. 10/310,720.
 Office Action dated May 4, 2007 issued in U.S. Appl. No. 10/310,720.
 Office Action dated Jan. 24, 2008 issued in U.S. Appl. No. 10/310,720.
 Notice of allowance dated Aug. 13, 2010, issued in U.S. Appl. No. 10/310,720.

* cited by examiner




Fig. 1

U.S. Patent

Mar. 13, 2012

Sheet 2 of 22

US 8,133,230 B2




Fig. 2




Fig. 3

U.S. Patent

Mar. 13, 2012

Sheet 4 of 22

US 8,133,230 B2




Fig. 4




Fig. 5

U.S. Patent

Mar. 13, 2012

Sheet 6 of 22

US 8,133,230 B2




Fig. 6




Fig. 6A




Fig. 7




Fig. 8

U.S. Patent

Mar. 13, 2012

Sheet 9 of 22

US 8,133,230 B2




Fig. 9




Fig. 10




Fig. 11

U.S. Patent

Mar. 13, 2012

Sheet 12 of 22

US 8,133,230 B2




Fig. 12




Fig. 13

U.S. Patent

Mar. 13, 2012

Sheet 14 of 22

US 8,133,230 B2




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23

US 8,133,230 B2

1

**BONE ALIGNMENT IMPLANT AND
METHOD OF USE****CROSS-REFERENCE TO RELATED
APPLICATIONS**

This application is a divisional application of U.S. patent application Ser. No. 10/310,720, filed Dec. 4, 2002, which is incorporated herein by reference.

BACKGROUND OF THE INVENTION**1. The Field of the Invention**

The present invention relates to the design and method of use for an implant to help realign angular and rotational deformities in long bones in patients with active growth plates.

2. Related Technology

As a result of congenital deformation, traumatic injury or other causes, long bones such as the femur, tibia and humerus may grow out of alignment, causing deformity of the limb and biomechanical abnormalities. While some deformities are asymptomatic or may resolve spontaneously, it is often necessary to intervene surgically to realign these limbs. For the patients requiring surgical intervention, both osteotomy with realignment of the bone and epiphyseal stapling are currently accepted methods of treatment.

One common method of surgical bone realignment is by means of an osteotomy, or cutting of the bone, followed by realignment of the bone. In some procedures the bone is cut laterally, transverse to the longitudinal axis of the bone. Then the bone is realigned. A bone graft is then placed in the resulting wedge space. The bone and the bone graft are stabilized by orthopedic fragment fixation implants such as screws and bone plates. In an alternative osteotomy procedure, a bone wedge is removed. The bone is realigned, and similar implants are used to secure the bone. A third method of deformity correction via osteotomy is to first cut the bone, then apply an external frame attached to pins drilled through the skin and into the bone. By adjusting the frame, either intraoperatively or postoperatively, the bone is straightened.

Because osteotomy methods require a relatively large incision to create bone cuts, they are relatively invasive; they disrupt the adjacent musculature and may pose a risk to the neurovascular structures. An additional disadvantage of these procedures is the potential risk of damage to the growth plate, resulting in the disruption of healthy limb growth. Consequently, this procedure may be reserved for bone alignment in skeletally mature patients in whom the growth plates are no longer active.

One less invasive method of bone alignment involves the placement of constraining implants such as staples around the growth plate of the bone to restrict bone growth at the implant site and allow the bone to grow on the opposite side. First conceived in 1945 by Dr. Walter Blount, this method is known as epiphyseal stapling. Typically epiphyseal stapling is more applicable in young pediatric patients and adolescents with active growth plates. A staple is placed on the convex side of an angular deformity. Since the bone is free to grow on the concave side of the deformity, the bone tends to grow on the unstapled side, causing the bone to realign over time. Once the bone is aligned, the constraining implants are typically removed.

As long as the growth plate is not disturbed, this type of intervention is generally successful. However, the procedure must be done during the time that the bone is still growing, and the physiodynamics of the physis (growth plate) must not

2

be disturbed. With proper preoperative planning and placement of the implants, the surgeon can use the implants to slowly guide the bone back into alignment.

The implants currently used in epiphyseal stapling procedures are generally U-shaped, rigid staples. The general design has essentially remained the same as those devised by Blount in the 1940's. Since these implants are rigid, they act as three-dimensional constraints prohibiting expansion of the growth plate. They are not designed to allow flexibility or rotation of the staple legs with the bone sections as the bone is realigned. Due to the constraints of these staple implants, the planning associated with the placement of the implants is overly complicated. Consequently, the surgeon must not only determine where to position the implant across the physis, but also must account for the added variables of implant stiffness, implant strength and bone-implant interface rupture.

The force associated with bone growth causes bending of these implants proportionate to their stiffness. Depending on the strength of the implant, these loads could eventually cause the implants to fracture under the force of bone realignment. This can make them difficult or impossible to remove. These same forces can also cause the implants to deform, weakening the bone-to-implant interface. This weakening may result in migration of the implant out of the bone, risking damage to the adjacent soft tissues and failure of the procedure.

SUMMARY OF THE INVENTION

The invention relates to an orthopedic bone alignment implant system that includes a guide wire, a link and bone fasteners. The guide wire serves to locate the growth plate under fluoroscopic guidance. The bone fasteners and the link function together as a tether between bone segments on opposite sides of the physis. As the bone physis generates new physeal tissue, the bone alignment implant tethers between engagers on the bone segments. This tethering principle guides the alignment of the bone as it grows.

Although applicable in various orthopedic procedures involving fracture fixation, the bone alignment implant is also applicable to the correction of angular deformities in long bones in which the physis is still active.

The distal end of the guide wire is used to locate the physis. Once its tip is placed in the physis, it is driven partly into the physis to function as a temporary guide for the link. The delivery of the implant over the guide wire assures that the link is properly placed with the bone fasteners on opposite sides of the physis. This will minimize the chance of damaging the physis throughout bone realignment. The link is then placed over the guide wire and oriented such that openings through the link for the bone fasteners are on either side of the physis. For pure angular correction, these openings would be collinear with the long axis of the bone; for rotational correction, they would be oblique to its axis.

The bone fasteners are then placed through the openings in the link and into the bone, connecting the sections of bone on opposite sides of the physis with the implant. Alternatively, guide pins can be used to help align cannulated fasteners.

The implant is designed such that it partially constrains the volume of the bone growth on the side of the physis that it is placed. The implant guides the growth of new bone at the physis such that the growth direction and resulting alignment is controlled. The implant limits the semi-longitudinal translation of the bone fasteners yet allows for the bone fasteners to freely rotate with the bone segments as the angular or torsional deformity is straightened.

In some embodiments of this invention, both the link and the fasteners are rigid, but the connection between them

US 8,133,230 B2

3

allows for relative movement of the fasteners. In other embodiments the link is flexible allowing the fasteners to move with the bone sections. In other embodiments, the fasteners have flexible shafts allowing only the bone engager of the fasteners to move with the bone sections. In still other embodiments, both the link and the shafts of the fasteners are flexible, allowing movement of the bone sections.

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments of the present invention will now be discussed with reference to the appended drawings. It is appreciated that these drawings depict only typical embodiments of the invention and are therefore not to be considered limiting of its scope.

FIG. 1 is an anterior view of the knee showing a genu valgum deformity (knee knocking) in the femur and the insertion of a guide wire approximately parallel to the physis;

FIG. 2 is a sagittal view of that described in FIG. 1 showing the placement of the guide wire in the physis;

FIG. 3 is an anterior view of the knee showing the placement of a link and drill guide over the guide wire and the use of the guide to place two guide pins for fasteners on opposite sides of the physis;

FIG. 4 is a sagittal view of the placement of the link described in FIG. 3 showing the position of the two guide pins on opposite sides of the physis;

FIG. 5 is an alternative method of applying the link over the guide wire in which the link is placed first, then the fasteners are placed through the openings in the link;

FIG. 6 is a sagittal view of the link placement also shown in FIG. 5;

FIG. 6A is a top plan view of the link shown in FIG. 6;

FIG. 7 is an anterior view showing an alternative method of drilling of holes in the bone over the guide pins to prepare the bone for the fasteners;

FIG. 8 is an anterior view of the link showing the placement of the fasteners through the link and into the bone segments;

FIG. 9 is a sagittal view of the fasteners and link described in FIG. 8;

FIG. 10 is an anterior view as seen after the physal tissue has grown and the bone alignment implant assembly has been reoriented as the bone is realigned;

FIG. 11 is a sagittal view of the bone alignment implant placed on a rotational deformity;

FIG. 12 is the same sagittal view described in FIG. 11 after the rotational deformity has been corrected;

FIG. 13 is a perspective view of a threaded fastener;

FIG. 14 is a perspective view of a barbed fastener;

FIG. 15 is a perspective view of an alternative embodiment of the bone alignment implant with rigid link and fasteners, with joints allowing restricted movement between them;

FIG. 16 is a perspective view of an alternative embodiment of the bone alignment implant showing a flexible midsection of the link with rigid material surrounding the openings;

FIG. 17 is a perspective view of an alternative embodiment of the bone alignment implant showing a flexible midsection of the link made from a separate flexible member with rigid material surrounding the openings;

FIG. 18 is a perspective view of an alternative embodiment of the bone alignment implant showing flexible woven material throughout the body of the link with reinforcement grommets surrounding the openings;

FIG. 19 is a perspective view of an alternative embodiment of the bone alignment implant showing the link made from a flexible band of material;

4

FIG. 20 is a perspective view of an alternative embodiment of the bone alignment implant showing the link made from a flexible ring of braided material that is joined in the midsection, forming two openings;

FIG. 21 is a side view of an alternative embodiment of the bone alignment implant showing bone fasteners that have flexible shaft sections;

FIG. 22 is a side view of an alternative embodiment of the bone alignment implant showing two barbed bone fasteners attached to a flexible link; and

FIG. 23 is a side view of an alternative embodiment of the bone alignment implant showing one barbed bone fastener and one threaded bone fastener connected to a flexible link.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to FIG. 1, a schematic anterior view of the human knee joint is depicted in which a distal femur 10 is proximal to a proximal tibia 5 and a proximal fibula 6. A distal femoral physis 1, or growth plate, separates a distal epiphyseal section 3 from a proximal metaphyseal section 2 of the distal femur 10. Likewise a proximal tibial physis 1' separates a proximal epiphyseal section 3' from a metaphyseal section 2' of the proximal tibia 5 and a proximal fibula physis 1" separates a proximal epiphyseal section 3" of a proximal fibula 6 from a metaphyseal section 2" of the proximal fibula 6. Although the invention described herein is adaptable to nearly all of the long bones in the body, only the example of correcting one type of an angular deformity in the distal femur will be described in detail. The principles described herein can be adapted to other deformities and other bones such as the tibia, fibula, humerus, radius and ulna.

By example, an angular deformity 4 in the femur 10 known as genu valgum or knock-knee is shown in FIG. 1. The angular deformity 4 is the angle between a pretreatment longitudinal axis 12 of the femur 10 and a post treatment projected longitudinal axis 13 of the femur 10. A bone alignment implant will be placed on the medial side of the femur 10. In this case, the medial side of the femur 10 is curved in a convex arc. Hence, this side of the deformity is called a convex side 16 because the angular deformity 4 bends the femur 10 in a curve that is angled away from or convex with respect to the medial side. A concave side 17 is on the opposite side of the femur 10. Likewise, the angular deformity 4 is angled towards the concave side 17.

A guide wire 8, as shown in FIG. 1, is used to locate the physis and guide the bone alignment implant to the surgical site. The guide wire 8 comprises a long axis 11, a distal section 9 that is shaped to fit into the physal tissue, and a periphery 14 that is typically a constant size and shape. In this case, the shape of the guide wire 8 along the long axis 11 is essentially cylindrical so the shape of the periphery 14 is round and does not change except for in the distal section 9. However, the periphery 14 can be a variable cross-section that changes shape or size along the length of the long axis 11.

In this example, the long axis 11 of the guide wire 8 is placed into and approximately parallel with the physis 1 and is aligned approximately in the same plane as the angular deformity 4. As shown in FIG. 1, the distal section 9 of the guide wire 8 is partly inserted into the physis 1. Since the cartilaginous physis 1 is of less density than the surrounding bone, the surgeon can either poke the distal section of the guide wire 8 into the bone until the physis 1 is located, or the surgeon can use fluoroscopic x-ray (not shown) or other bone density detection means (not shown) to determine the location of the physis 1 relative to the distal section of the guide

US 8,133,230 B2

5

wire 8 to place the guide wire 8 in a direction that is approximately parallel with the physis 1.

FIG. 2 is a sagittal view approximately perpendicular to the anterior view described in FIG. 1. For reference, a patella 7 is shown on the anterior side of the femur 10 and tibia 5. For clarity, in this example the guide wire 8 is straight and has a constant round outer periphery 14. Consequently, only the outer periphery 14 of the guide wire 8 is shown and appears as a circle in FIG. 2. FIG. 2 shows the placement of the guide wire 8 in the physis between the femoral metaphyseal section 2 and the distal femoral epiphyseal section 3. This is the preferred placement of the guide wire 8. The guidewire 8 is used to locate an area in the physis that will eventually be bridged by the bone alignment implant 9 that will tether between two sections of the bone. In FIG. 2, the two sections of bone that will be tethered by the bone alignment implant 9 are the distal femoral proximal epiphyseal section 3 and the femoral metaphyseal section 2.

FIG. 3 is an anterior view of the knee showing the placement of a link 30 and a guide 20 over the guide wire 8. The guide 20 is used to place a first guide pin 40 and a second guide pin 50 on opposite sides of the physis 1. The link 30 has an outer periphery 34 that defines the outer material bounds of the link 30, a bone side 37 that is the side of the link that is placed against the bone, a first opening 31 and a second opening 32.

First, the guide 20 and link 30 are placed over the guide wire 8 by guiding the guide wire 8 over a guide opening 33 in the link 30 and the guide hole 23 in the guide 20. Then the first guide pin 40 is driven through a first hole 21 in the guide 20 and through the first opening 31 in the link 30 into the metaphyseal bone 2, and the second guide pin 50 is driven through a second hole 22 in the guide 20 and the second opening 32 in the link 30 into the distal epiphyseal section 3. Once the first guide pin 40 and the second guide pin 50 are placed, the guide 20 is removed.

FIG. 4 is a sagittal view of the placement of the link 30 described in FIG. 3. The position of the first guide pin 40 is through the first opening 31 in the link 30. The position of the second guide pin 50 is through the second opening 32 in the link 30. The guide pin 40 and guide pin 50 are on opposite sides of physis 1. Likewise, the first opening 31 and the second opening 32 are on opposite sides of the physis 1.

FIG. 5 is an anterior view showing an alternative embodiment of the link 30 placed on the medial femur 10. In this embodiment, a first set of spikes 35 and a second set of spikes 36 on the bone side 37 of the link 30 help to keep the link 30 in place prior to the placement of a first bone fastener 70 and a second bone fastener 80. The first set of spikes 35 is positioned near the first opening 31 and the second set of spikes 36 is positioned near the second opening 32 in the link 30. Hence, as the link 30 is placed across the physis 1, the first set of spikes 35 contacts the metaphyseal section 2 and the second set of spikes 36 contacts the epiphyseal section 3. In this embodiment, the first bone fastener 70 is placed through the first opening 31 in the link 30 then into the metaphyseal section 2 and the second bone fastener 80 is placed through the second opening 32 in the link 30 then into the epiphyseal section 3.

FIG. 6 is a sagittal view of the link 30 on the femur 10 showing the location of the first set of spikes 35 near the first opening 31 on the metaphyseal section 2 side of the physis 1 and the location of the second set of spikes 36 near the second opening 32 on the epiphyseal section 3 side of the physis 1.

As shown in FIG. 6A, link 30 can further be defined as having a top surface 150 that is opposite the bottom surface 37. Bottom surface 37 was also previously referenced as bone

6

side 37 in FIG. 3. Both bottom surface 37 and top surface 150 extend between a first side edge 152 and an opposing second side edge 154. Likewise, both bottom surface 37 and top surface 150 longitudinally extend between a first end 156 and an opposing second end 158. A first recess 162 is centrally formed on first side edge 152 while a second recess 164 is centrally formed on second side edge 154.

In the embodiment depicted, guide opening 33 is centrally disposed between first opening 31 and second opening 32 with guide opening 33 being smaller than openings 31 and 32. Each of openings 31, 32, and 33 are aligned along a central longitudinal axis 160 that extends between first end 156 and second end 158. Recesses 162 and 164 can be positioned on opposing sides of guide opening 33 such that a linear line 166 extending between recesses 162 and 164 intersect guide opening 33. The length of linear line 166 extending between recesses 162 and 164 is a first width of link 30. Linear line 166 is shown in the present embodiment as extending orthogonal to longitudinal axis 160.

Link 30 can also be formed so that a linear line 168 can extend between side edges 152 and 154 so as to intersect with first opening 31. Line 168 is shown extending orthogonal to longitudinal axis 160 and measures a second width of link 30. Because of recesses 162 and 164, the first width is smaller than the second width. A linear line 170 can similarly extend between side edges 152 and 154 so as to intersect with second opening 32. Line 170 is shown extending orthogonal to longitudinal axis 160 and measures a third width of link 30. The first width of link 30 is smaller than the third width.

FIG. 7 is an anterior view of the placement of the link 30, first guide pin 40, and second guide pin 50 as previously described in the sagittal view shown in FIG. 4. FIG. 7 also shows a bone preparation tool 60 that can be used to prepare a bore 28 in the bone prior to the first fastener 70 or second fastener 80 placements. The bone preparation tool 60 can be a drill, tap, rasp, reamer, awl or any tool used to prepare a bore in bone tissue for a fastener. The bone preparation tool 60 is used to prepare a bore 28 on the bone near the second opening in the epiphyseal section 3 for the second fastener 80. A bone preparation tool 60 can also be used to prepare the bone in the metaphyseal section 2 for the first fastener 70. In the case of the example shown in FIG. 7, the bone preparation tool 60 is placed over the second guide pin 50, through the second opening 32, and into the epiphyseal section 3. However, the bone preparation tool 60 can also be placed directly through the second opening 32 without the guidance of the second guide pin 50. The bone preparation tool 60 is used if needed to prepare the bone to receive the first fastener 70 and second fastener 80. Once the bone is prepared, the bone preparation tool 60 is removed from the surgical site.

The first fastener 70 is then placed over the first guide pin 40, through the first opening 31, and into the metaphyseal section 2. The second fastener 80 is placed over the second guide pin 50, through the second opening 32 and into the epiphyseal section 3. If the first guide pin 40 and second guide pin 50 are not used, the first fastener 70 is simply driven through the first opening 31 and the second fastener 80 is simply driven through the second opening 32 without the aid of the guide pins 40 and 50.

FIG. 8 is an anterior view showing the position of a bone alignment implant 15 on the convex side 16 of the angular deformity 4. The bone alignment implant 15 comprises the link 30, the first fastener 70, and the second fastener 80. The bone alignment implant 15 functions as a tether connecting the metaphyseal section 2 and the epiphyseal section 3. The first fastener 70 and the second fastener 80 are placed on opposite sides of the physis 1. As the physis 1 generates new

US 8,133,230 B2

7

physeal tissue **90**, the physeal tissue **90** will fill in between the metaphyseal section **2** and the epiphyseal section **3** in the space subjected to the least resistance. The bone alignment implant **15** restricts the longitudinal movement between the epiphyseal section **3** and the metaphyseal section **2** on the convex side **16** of the angular deformity **4**.

FIG. **9** shows the sagittal view of that described for FIG. **8**. The bone alignment implant **15** functioning as a tether restricting the longitudinal movement between the epiphyseal section **3** and the metaphyseal section **2**.

As shown in FIG. **10**, in a patient with an active physis, the newly generated physeal tissue **90** fills in more on the side of the bone that is not tethered by the bone alignment implant **15**. Hence, a net gain **95** of physeal tissue **90** forces the bone to align in the direction of an angular correction **97**.

Select embodiments of the bone alignment implant **15** comprise the first fastener **70** having a first engager **75**, the second fastener **80** having a second engager **85** and the link **30**. The link **30**, the first fastener **70** and the second fastener **80** function together as tethers between a first engager **75** on the first fastener **70** and a second engager **85** on the second fastener **80**, guiding movement between the epiphyseal section **3** and metaphyseal section **2** of bone.

FIG. **11** and FIG. **12** show an example of using the bone alignment implant to correct a torsional abnormality between the metaphyseal section **2** and the epiphyseal section **3**. The link **30** is placed across the physis **1** at an angle **18** that is related to the amount of torsional deformity between the bone sections **2** and **3**. As the physis **1** generates new physeal tissue **90**, the bone alignment implant **15** guides the direction of growth of the bone to allow a torsional correction **98** of the bone alignment.

Different fastening devices designs that are well known in the art can be functional as fasteners **70** and **80**. The basic common elements of the fasteners **70** and **80** are seen in the example of a threaded fastener **100** in shown in FIG. **13** and a barred fastener **120** shown in FIG. **14**.

The threaded fastener **100**, and the barred fastener **120** both have a head **73** comprising a head diameter **74**, a drive feature **72** and a head underside **71**. The drive feature in the threaded fastener **100** is an internal female hex drive feature **102**. The drive feature in the barred fastener **120** is an external male drive feature **122**. The shape of the underside **71** of the barred fastener **120** is a chamfer cut **124** and the underside of the threaded fastener **100** is a rounded cut **104**. The underside **71** shape of both the threaded fastener **100** and the barred fastener **120** examples are dimensioned to mate with shapes of the first opening **31** and the second opening **32** in the link **30**.

Directly adjacent to the head **72** on both threaded fastener **100** and the barred fastener **120** is a fastener shaft **79** with a shaft diameter **76**. Protruding from the shaft **79** is the aforementioned engager **75** with a fixation outer diameter **77**. This fixation diameter varies depending on the bone that is being treated and the size of the patient. Typically this diameter is from 1 mm to 10 mm. The shaft diameter **76** can be an undercut shaft **125**, as shown in the barred fastener **120**, with a diameter **76** smaller than the fixation outer diameter **77**. The shaft diameter can also be a run out shaft **105** as shown in the threaded fastener **100** with a diameter **76** larger than or equal to the fixation diameter **77**. In either case, the shaft diameter **76** is smaller than the head diameter **74**. This allows fasteners **70** and **80** to be captured and not pass completely through the openings **31** and **32** in the link **30**.

In the case of the threaded fastener **100**, the engager **75** comprises at least one helical thread form **103**. Although the example of a unitary continuous helical thread **103** is shown,

8

it is understood that multiple lead helical threads, discontinuous helical threads, variable pitch helical threads, variable outside diameter helical threads, thread-forming self-tapping, thread-cutting self-tapping, and variable root diameter helical threads can be interchanged and combined to form an optimized engager **75** on the threaded fastener **100**. The engager **75** on the barbed fastener **120** is shown as a uniform pattern of connected truncated conical sections **123**. However, it is understood that different barbed fastener designs known in the art such as superelastic wire arcs, deformable barbs, radially expandable barbs, and barbs with non-circular cross-sections can be interchanged and combined to form an optimized engager **75** on the barbed fastener **120**.

Protruding from the engager **75** at the distal end of both the threaded fastener **100** and the barbed fastener **120** is a fastener tip **78**. The fastener tip **78** can either be a smooth conical tip **126** as shown in the barbed fastener **120**, or a cutting tip **106** as shown on the threaded fastener **100**. Although a cutting flute tip is shown as the cutting tip **106** on the threaded fastener, other cutting tips designs including gimble and spade tip can be used.

In the example of the barbed fastener **120**, a canulation bore **128** passes through the head **73**, the shaft **79**, the engager **75**, and the tip **78**. This canulation bore **128** allows placement of the fasteners **70** and **80** over the guide pins **40** and **50**. Although not shown on the example of the threaded fastener **100** in FIG. **13**, it is understood that the fasteners **70** and **80**, regardless of their other features, can either be of the cannulated design shown in the barbed fastener **120** example or a non-cannulated design as shown in the threaded fastener **100** example.

Fasteners **70** and **80** can be made in a variety of different ways using a variety of one or more different materials. By way of example and not by limitation, fasteners **70** and **80** can be made from medical grade biodegradable or non-biodegradable materials. Examples of biodegradable materials include biodegradable ceramics, biological materials, such as bone or collagen, and homopolymers and copolymers of lactide, glycolide, trimethylene carbonate, caprolactone, and p-dioxanone and blends or other combinations thereof and equivalents thereof. Examples of non-biodegradable materials include metals such as stainless steel, titanium, Nitinol, cobalt, alloys thereof, and equivalents thereof and polymeric materials such as non-biodegradable polyesters, polyamides, polyolefins, polyurethanes, and polyacetals and equivalents thereof.

All the design elements of the threaded fastener **100** and barred fastener **120** are interchangeable. Hence either of the fasteners **70** and **80** can comprise of any combination of the design elements described for the threaded fastener **100** and the barred fastener **120**. By way of one example, the first fastener **70** can be made from a bioabsorbable copolymer of lactide and glycolide and structurally comprise an external male drive feature **122**, a run out shaft **105**, a multiple-lead, non-continuous helically threaded engager **75**, with a cutting flute tip **106** and a continuous canulation **128**. Likewise the second fastener **80** can be made from a different combination of the features used to describe the threaded fastener **100** and the barred fastener **120**.

Although the examples of barbed connected truncated conical sections **123** and helical thread forms **103** are shown by example to represent the bone engager **75**, it is understood that other means of engaging bone can be used for the engager **75**. These means include nails, radially expanding anchors, pressfits, tapers, hooks, surfaces textured for biological ingrowth, adhesives, glues, cements, hydroxyapatite coated engagers, calcium phosphate coated engagers, and engagers with tissue engineered biological interfaces. Such means are

US 8,133,230 B2

9

known in the art and can be used as alternative bone engagement means for the first bone engager **75** on the first fastener **70** or the second bone engager **85** on the second fastener **80**.

Different embodiments of the bone alignment implant **15** invention allow for different means of relative movement between the two bone sections **2** and **3**. Nine embodiments of the bone alignment implant **15** are shown in FIG. **15** through FIG. **23**. These embodiments are labeled **15A** through **15I**.

In a rigid-bodies embodiment **15A** shown in FIG. **15**, both the link **30** and the fasteners **70** and **80** are rigid, but a first connection **131** and a second connection **132** between each of them allows for relative movement between the link **30** and the fasteners **70** and **80** resulting in relative movement between the bone sections **2** and **3**. In embodiments **15B**, **15C**, and **15D** of this invention shown in FIG. **16**, FIG. **17** and FIG. **18**, the link **30** is deformable allowing the fasteners **70** and **80** to move with the bone sections **2** and **3**. In embodiments **15E** and **15F** shown in FIG. **19** and FIG. **20**, the connections between the link **30** and the fasteners **70** and **80** along with the deformable link **30** allow the fasteners **70** and **80** to move with the bone sections **2** and **3**. In an embodiment **15G** shown in FIG. **21**, the fasteners **70** and **80** are deformable allowing movement of the bone sections **2** and **3**. In embodiments **15H** and **15I** shown in FIG. **22** and FIG. **23**, the fasteners **70** and **80** are fixed to a flexible link **30**.

A rigid-bodies embodiment **15A** of the bone alignment implant **15** is shown in FIG. **15**. In the rigid-bodies embodiment **15A**, the link **30** is a rigid link **130**. In the rigid bodies embodiment **15A**, the first fastener **70** is free to rotate about its axis or tilt in a first tilt direction **60** or a second tilt direction **61** and is partially constrained to move in a longitudinal direction **62** by the confines of the size of the first opening **31** and the first shaft diameter **77**, and partially constrained to move in the axial direction by the confines of the size of the first opening and the diameter **74** of the head **73** of the first fastener **70**. The first opening **31** is larger in the longitudinal direction **62** than is the shaft diameter **77** of the first fastener **70**. This allows for relative movement at the first joint **131** in a combination of tilt in the first direction **60**, tilt in the second direction **61**, and translation in the axial direction **63**.

Similar tilt and translation is achieved between the second fastener **80** and the link **30** at the second joint **132**. The second fastener **80** is also free to rotate or tilt in a first tilt direction **60'** or a second tilt direction **61'** and is partially constrained to move in a longitudinal direction **62'** by the confines of the size of the second opening **32** and the shaft diameter of the second fastener **80**. The second opening **31** is larger in the longitudinal direction **62'** than is the shaft diameter of the second fastener **80**. This allows for relative movement at the second joint **132** in a combination of tilt in the first direction **60'** and tilt in the second direction **61'** and limited translation in the axial direction **63'**.

The combination of relative movement between the first joint and the second joint allows for relative movement between the bone sections **2** and **3** when the rigid bodies embodiment **15A** of the bone alignment implant **15** is clinically applied across an active physis **1**.

A flexible link embodiment **15B** of the bone alignment implant **15** is shown in FIG. **16**. In the deformable link embodiment **15B**, the link **30** is represented by a deformable link **230** that allows deformation of the sections **2** and **4** as the physis **1** grows in a first bending direction **64** and a second bending direction **65**. However, the maximum length between the first opening **31** and the second opening **32** of the deformable link **230** limits the longitudinal displacement **62** between the head **73** of the first fastener **70** and the longitudinal displacement **62'** between the head **83** of the second fastener **80**.

10

Since the heads **73** and **83** are coupled to the respective bone engagers **75** and **85**, and the bone engagers **75** and **85** are implanted into the respective bone segments **2** and **3**, the maximum longitudinal displacement of the bone segments **2** and **3** is limited by the deformed length between the first opening **31** and second opening **32** of the link **30**, and the flexibility and length of the fasteners **70** and **80**.

Also shown in FIG. **16** is a material differential area **38** on the link **30**. The material differential area **38** is an area on the link **30** where material is either added to the link **30** or removed from the link **30** in relationship to the desired mechanical properties of a central section **39** of the link **30**. The central section **39** is made stiffer by adding material to the material differential area **38**.

The central section **39** is made more flexible by removing material from the material differential area **38**. Similarly the central section **39** is made stiffer by holding all other variables constant and decreasing the size of the guide opening **33**. The central section **39** is made more flexible by increasing the size of the guide opening **33**. Hence the desired stiffness or flexibility of the link **30** is regulated by the relative size of the material removed or added at the material differential areas **37** and **38** and the relative size of the guide opening **33** with respect to the outer periphery **34** in the central section **39** of the link **30**.

It is also understood that the relative stiffness and strength of the link **30** and structural elements such as the central section **39** is dependent on the material from which it is made. The link **30** and structural elements such as the central section **39** therein can be made in a variety of different ways using one or more of a variety of different materials. By way of example and not by limitation, the central section **39** can be made from medical grade biodegradable or non-biodegradable materials. Examples of biodegradable materials include biodegradable ceramics, biological materials, such as bone or collagen, and homopolymers and copolymers of lactide, glycolide, trimethylene carbonate, caprolactone, and p-dioxanone and blends or other combinations thereof and equivalents thereof. Examples of non-biodegradable materials include metals such as titanium alloys, zirconium alloys, cobalt chromium alloys, stainless steel alloys, Nitinol alloys, or combinations thereof, and equivalents thereof and polymeric materials such as non-biodegradable polyesters, polyamides, polyolefins, polyurethanes, and polyacetals and equivalents thereof.

FIG. **17** shows a flexible cable embodiment **15C** of the bone alignment implant **15**. The flexible cable embodiment **15C** comprises a flexible cable link **330** joined to the first fastener **70** by a first eyelet **306** on the first side **310** and joined to the second fastener **80** by a second eyelet **307** on the second side **311**. The first eyelet **306** has a first opening **331** through which the first fastener **70** passes. The second eyelet **307** has a second opening **332** through which the second fastener **80** passes. A flexible member **339** connects the first eyelet **306** to the second eyelet **307**. The flexible member **339** allows relative movement between the first eyelet **306** and the second eyelet **307**, except the longitudinal displacement **62** and **62'** is limited by the length between the first opening **331** and the second opening **332**. This is proportional to the length of the flexible member **339**.

The flexible member **339** is connected to the first eyelet **306** and the second eyelet **307** by means of joined connections **318** and **319**. These joined connections **318** and **319** are shown as crimped connections in this example. However, the flexible member **339** can be joined to the link **30** by other means such as insert molding, welding, soldering, penning, pressfitting, cementing, threading, or gluing them together.

US 8,133,230 B2

11

FIG. 18 shows a flexible fabric embodiment 15D of the bone alignment implant 15. The flexible fabric embodiment 15D comprises a flexible fabric link 430 joined to the first fastener 70 and the second fastener 80. The flexible fabric link 430 comprises a first grommet 406 on a first side 410 and joined to the second fastener 80 by a second grommet 407 on a second side 411. The first grommet 406 has a first opening 431 through which the first fastener 70 passes. The second grommet 407 has a second opening 432 through which the second fastener 80 passes. A flexible fabric 439 connects the first grommet 406 to the second grommet 407. The flexible fabric 439 allows relative movement between the first grommet 406 and the second grommet 407, except the longitudinal displacement 62 is limited by the length between the first opening 431 and the second opening 432. A guide hole grommet 433 may be employed to reinforce the guide pin opening 33.

The grommets function as reinforcement structures that prevent the flexible fabric from being damaged by the fasteners 70 and 80. The grommets can be made from medical grade biodegradable or non-biodegradable materials. Examples of materials from which the grommet can be made are similar to those bioabsorbable and non-biodegradable materials listed as possible materials for the fasteners 70 and 80.

The flexible fabric 439 comprises woven or matted fibers of spun medical grade biodegradable or non-biodegradable materials. A wide variety of materials may be used to make the flexible fabric 439. For example, wire, fibers, filaments and yarns made therefrom may be woven, knitted or matted into fabrics. In addition, even non-woven structures, such as felts or similar materials, may be employed. Thus, for instance, nonabsorbable fabric made from synthetic biocompatible nonabsorbable polymer yarns, made from polytetrafluorethylenes, polyesters, nylons, polyamides, polyolefins, polyurethanes, polyacetals and acrylic yarns, may be conveniently employed. Similarly absorbable fabric made from absorbable polymers such as homopolymers and copolymers of lactide, glycolide, trimethylene carbonate, caprolactone, and p-dioxanone and blends or other combinations thereof and equivalents thereof may be employed. Examples of non-biodegradable non-polymeric materials from which the flexible fabric can be made include metals such as stainless steel, titanium, Nitinol, cobalt, alloys thereof, and equivalents thereof.

A band embodiment 15E is shown in FIG. 19 in which a band 530 that is a continuous loop or band of material that functions as the link 30. The band embodiment 15E allows both movement at the first joint 131 and second joint 132 and allows deformation within the link 30. The shafts 79 of the first fastener 70 and second fastener 80 are both positioned in the inside 531 of the band 530. The band can be either a fabric band made from the same materials described for the flexible fabric 439 of the flexible fabric embodiment 15D, or the band 530 can be a unitary, continuous loop of a given biocompatible material such as a bioabsorbable polymer, non-biodegradable polymer, metal, ceramic, composite, glass, or biologic material.

In the band embodiment 15E, the band 530 tethers between the head 73 of the first fastener 70 and the head 83 of the second fastener 80 as the physal tissue 90 generates and the bone is aligned. One advantage of the band embodiment 15E is that after the desired alignment is obtained, the band 530 can be cut and removed without removing the fasteners 70 and 80. Furthermore, as with all of the embodiments of the bone alignment device 15A, 15B, 15C, 15D, 15F, 15G, 15H and 15I, the fasteners 70 and 80 can be made from a biodegradable material and left in place to degrade.

12

A crimped band embodiment 15F of the bone alignment device 15 is shown in FIG. 20. The crimped band embodiment 15F is similar to the band embodiment 15E in that it allows both movement at the first joint 131 and second joint 132. The crimped band embodiment 15F comprises a crimped band link 630 that comprises a band 632 that loops around the head 73 of the first fastener 70 and the head 83 of the second fastener 80. However, the link 30 in the crimped band embodiment 15F has an additional ferrule feature 631 comprising a loop of deformable material that brings a first side 634 and a second side 635 of the band together forming the first opening 31 and the second opening 32. A bore 633 in the midsection of the ferrule 631 passes through the crimped band link 630 to form the aforementioned guide pin hole 33.

As with the band embodiment 15E, an advantage of the crimped band embodiment 15F is that after the desired alignment is obtained, the band 632 can be severed across the boundaries of the first opening 31 and the boundaries of the second opening 32. This provides a means for the crimped band link 630 to be removed without removing the fasteners 70 and 80.

A deformable fastener embodiment 15G is shown in FIG. 21. The deformable fastener embodiment 15G comprises a first deformable fastener 770 with a deformable shaft 776, a link 30 and a second fastener 780. The second fastener 780 may also have a deformable shaft 786 as shown in the deformable fastener embodiment 15G. However, it may also have a nondeformable shaft. The second fastener 780 may also be in the design or material of any of the combinations of aforementioned threaded fasteners 100 or barbed fasteners 120. Likewise, the second fastener 780 can have a flexible shaft 786, as shown in the example of the deformable fastener embodiment 15G in FIG. 21, and the first fastener 770 can be in the design or material of any of the combinations of aforementioned threaded fasteners 100 or barbed fasteners 120.

The flexibility of the flexible shafts 776 and 786 of the fasteners 770 and 780 can be simply a result of the material selection of the flexible shaft 776 and 786, or can be the result of a design that allows for flexibility of the shaft. For example, the flexible shaft 776 and 786 can be manufactured from a material such as the aforementioned biocompatible polymeric materials or superelastic metallic materials such as Nitinol that would deform under the loads associated with bone alignment. The flexible shafts 776 and 786 could also be manufactured from biocompatible materials typically not considered to be highly elastic such as stainless steel, titanium, zirconium, cobalt chrome and associated alloys thereof, and shaped in the form of a flexible member such as cable, suture, mesh, fabric, braided multifilament strand, circumferentially grooved flexible shaft, filament, and yarn.

Connections 778 and 788 between the flexible shafts 776 and 786 and the associated engagers 775 and 785 of the fasteners 770 and 780 can be unitary and continuous, as is typically the case for fasteners 770 and 780 made entirely from the aforementioned biocompatible polymeric materials and superelastic metallic materials. The connections 778 and 788 can also be joined connections as is the case for flexible shafts 776 and 786 made from flexible members. Although the example of a pressfit connection is shown as the means of the connections 778 and 788 in the deformable fastener embodiment 15G shown in FIG. 21, these joined connections 778 and 788 can be crimped, welded, insert molded, soldered, panned, pressfit, cemented, threaded, or glued together.

Heads 773 and 783 are connected to the respective flexible shafts 776 and 786 by respective head connections 779 and 789. These head connections 779 and 789 can also be unitary and continuous, as again is typically the case of fasteners 70

US 8,133,230 B2

13

and **80** made entirely from the aforementioned biocompatible polymeric materials and superelastic metallic materials. The head connections **779** and **789** can also be joined connections, as is the case for flexible shafts **776** and **786** made from flexible members. Although the example of a pressfit connection is the means of the connections **779** and **789** in the deformable fastener embodiment **15G** shown in FIG. **21**, these joined connections **779** and **789** can also be crimped, insert molded, welded, soldered, penned, pressfit, cemented, threaded, or glued together.

Embodiments of the bone alignment implant **15** are shown in FIGS. **22** and **23** in which the first fastener **70** and second fastener **80** are fixedly joined to the link **30** that is flexible.

A paired fastener embodiment **15H** is shown in FIG. **22** in which similar designs of paired fasteners **870** and **880** are fixedly joined to a flexible link **830** by means of joined connections **831** and **832**. These joined connections **831** and **832** are shown as insert molded connections in this example in which the link is formed within the fastener by means of molding the molded fasteners **870** and **880** around the flexible link **830**. However, the paired fasteners **870** and **880** can be joined to the link **830** by other means such as crimping, welding, soldering, penning, pressfitting, cementing, threading, or gluing.

In the paired fastener embodiment **15H**, the first paired fastener **870** and the second paired fastener **880** are shown in FIG. **22** as barbed style fasteners similar to the aforementioned barbed fastener **120**. However, the paired fasteners **870** and **880** can also be similar to the aforementioned threaded fastener **100** or can comprise of any combination of the design elements described for the threaded fastener **100** and the barbed fastener **120**.

A non-paired fastener embodiment **15I** is shown in FIG. **23** in which different designs of fasteners **970** and **980** are fixedly joined to a flexible link **930** by means of joined connections **931** and **932**. These joined connections **931** and **932** are shown as insert molded connections in this example in which the link is formed within the fastener by means of molding the molded fasteners **970** and **980** around the flexible link **930**. However, the fasteners **970** and **980** can be joined to the link by other means such as crimping, welding, soldering, penning, pressfitting, cementing, threading, or gluing.

While the present invention has been disclosed in its preferred form, the specific embodiments thereof as disclosed and illustrated herein are not to be considered in a limiting sense as numerous variations are possible. The invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. No single feature, function, element or property of the disclosed embodiments is essential. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. The following claims define certain combinations and subcombinations that are regarded as novel and non-obvious. Other combinations and subcombinations of features, functions, elements and/or properties may be claimed through amendment of the present claims or presentation of new claims in this or a related application. Such claims, whether they are broader, narrower or equal in scope to the original claims, are also regarded as included within the subject matter of applicant's invention. All changes that come within the meaning and range of equivalency of the claims are to be embraced within their scope.

14

What is claimed is:

1. A method for correcting an angular deformity in a bone, the method comprising:

inserting a guide wire within a physis of a long bone of an arm or leg having an angular deformity, the physis separating a metaphyseal section of the bone from an epiphyseal section of the bone;

using the guide wire to guide a link to the physis, the link comprising a first opening and a spaced apart second opening passing therethrough;

advancing a first bone engager through the first opening and into the metaphyseal section of the bone; and

advancing the second bone engager through the second opening and into the epiphyseal section of the bone so that the link spans across the physis and restricts growth of the physal tissue of the physis adjacent to the link, the first bone engager and the second bone engager each being pivotably coupled to the link so that the first bone engager and the second bone engager pivot relative to the link as the physis generates more physal tissue.

2. The method as recited in claim **1**, wherein the guide wire extends through a guide opening formed on the link, the step of using the guide wire to guide the link to the physis comprising sliding the link over the guide wire to the physis.

3. The method as recited in claim **1**, wherein the step of using the guide wire to guide the link to the physis comprises: passing a free end of the guide wire through a guide opening on the link, the guide opening extending through and being completely encircled by the link; and sliding the link down the length of the guide wire to the physis.

4. The method as recited in claim **1**, wherein the steps of advancing the first bone engager and advancing the second bone engager comprise screwing the first bone engager into the metaphyseal section of the bone and screwing the second bone engager into the epiphyseal section of the bone.

5. The method as recited in claim **4**, further comprising allowing the physis to generate more physal tissue so that distal ends of the first bone engager and the second bone engager are further separated by the more physal tissue and the angular deformity of the bone is reduced.

6. The method as recited in claim **1**, further comprising allowing the physis to generate more physal tissue so that distal ends of the first bone engager and the second bone engager are increasingly separated so as to cause bending of the link between the first bone engager and the second bone engager.

7. The method as recited in claim **1**, further comprising removing the first bone engager and the second bone engager from the bone after the physis has generated sufficient physal tissue to reduce the angular deformity of the bone.

8. The method as recited in claim **1**, further comprising performing the steps of advancing the first bone engager and advancing the second bone engager when the bone is free of any fractures.

9. A method for correcting an angular deformity in a bone, the method comprising:

positioning a link so that the link spans across a physis of a bone, the bone having an angular deformity;

advancing a first bone engager through a first opening on the link and into a metaphyseal section of the bone so that the first bone engager secures the link to the metaphyseal section, the metaphyseal section being located on one side of the physis;

advancing a second bone engager through a second opening on the link and into an epiphyseal section of the bone so that the second bone engager secures the link to the

US 8,133,230 B2

15

epiphyseal section, the epiphyseal section being located on an opposite side of the physis, the link thereby restricting the growth of physeal tissue of the physis adjacent to the link; and
allowing the physis to generate more physeal tissue on a side of the bone opposite the link so that the angular deformity of the bone is reduced, the first bone engager and the second bone engager each being pivotably coupled to the link so that the first bone engager and the second bone engager pivot relative to the link as the physis generates more physeal tissue.
10. The method as recited in claim 9, further comprising removing the link from the bone after the angular deformity of the bone is reduced.
11. The method as recited in claim 9, wherein the steps of advancing the first bone engager and advancing the second bone engager comprise screwing the first bone engager into the metaphyseal section of the bone and screwing the second bone engager into the epiphyseal section of the bone.
12. The method as recited in claim 9, further comprising allowing the physis to generate more physeal tissue so that distal ends of the first bone engager and the second bone engager are increasingly separated so as to cause bending of the link between the first bone engager and the second bone engager.
13. The method as recited in claim 9, further comprising performing the step of positioning the link when the bone is free of any fractures.
14. The method as recited in claim 9, wherein the step of positioning the link comprises:
inserting a guide wire within the physis of the bone; and
using the guide wire to guide the link to the physis.

16

15. The method as recited in claim 14, wherein the step of using the guide wire to guide the link to the physis comprises: passing a free end of the guide wire through a guide opening on the link; and
sliding the link down the length of the guide wire to the physis.
16. A method for correcting an angular deformity in a bone, the method comprising:
positioning a link so that the link spans across a physis of a long bone of an arm or leg, the bone having an angular deformity;
screwing a first bone engager into a metaphyseal section of the bone so that the first bone engager secures the link to the metaphyseal section, the metaphyseal section being located on one side of the physis;
screwing a second bone engager into an epiphyseal section of the bone so that the second bone engager secures the link to the epiphyseal section, the epiphyseal section being located on an opposite side of the physis, the link thereby restricting the growth of physeal tissue of the physis adjacent to the link; and
allowing the physis to generate more physeal tissue on a side of the bone opposite the link so that the angular deformity of the bone is reduced, the first bone engager and the second bone engager each being pivotably coupled to the link so that the first bone engager and the second bone engager pivot relative to the link as the physis generates more physeal tissue.

* * * * *